

## GEN-SEP™

The Gen-Sep™ is used in conjunction with a Vernalift muffler on generator sets. The water drain from the Gen-Sep™ can be located below the water line to eliminate irritating water splash during overnight moorings.



PART #	A1	A2	H	J	K
	IN/OUT	DRAIN	HGT	WIDTH	DEPTH
	IN/MM	IN/MM	IN/MM	IN/MM	IN/MM
1020150	1.50 / 38	1.25 / 32	15.63 / 397	12.38 / 31	5.03 / 128
1020162	1.62 / 41	1.25 / 32	15.63 / 397	12.38 / 314	5.03 / 128
1020200	2.00 / 51	1.50 / 38	15.63 / 397	12.38 / 314	5.03 / 128
1020250	2.50 / 64	1.50 / 38	20.50 / 521	17.50 / 445	7.00 / 178
1020300	3.00 / 76	1.50 / 38	20.50 / 521	17.50 / 445	7.00 / 178
1020350	3.50 / 89	2.00 / 51	27.00 / 686	23.50 / 597	9.00 / 229
1020400	4.00 / 102	2.50 / 64	27.00 / 686	23.50 / 597	9.00 / 229
1020450	4.50 / 114	2.50 / 64	30.00 / 762	28.00 / 711	7.25 / 184
1020500	5.00 / 127	3.00 / 76	30.00 / 762	28.00 / 711	7.25 / 184

